

REMARKS

Claim Rejections under 35 U.S.C. §103

The Office Action indicated that claims 2, 4, 6, 7, 9, 12, 14, 15, 16, 17, 19, 22 and 24-27 would be allowable if rewritten in independent form including all of the limitations of the base claim and any intervening claims. However, the Office Action rejected claims 1, 3, 5, 8, 11, 13, 18, 20, 21 and 23 under 35 U.S.C. 103 as being unpatentable over U.S. Published Application No. 2003/0189952 to Long et al. (the Long reference) in view of US Patent 6,678,316 to Helms et al. (the Helms reference). Applicants respectfully traverse this rejection because neither the Long reference or the Helms reference, either alone or in combination, disclose or suggest the elements of the these claims.

Independent Claim 1 and Dependent Claims 2 through 7

First, with respect to the Long reference, it fails to disclose or suggest the requirements of claim 1 of, “transmitting, by a remote DSL transceiver, first signals containing even numbered carriers for a predetermined period of time to initiate the DSL handshaking to produce R-ETONES-REQ, wherein the first signals include periodic phase reversal; detecting, by a central office DSL transceiver, the R-ETONES-REQ to produce detected R-ETONES-REQ; determining, by the central office DSL transceiver, alignment of a hyperframe in accordance with a Time Compression Multiplexing – Integrated Service Digital Network (TCM-ISDN) Timing Reference (TTR); transmitting, by the central office DSL transceiver, first response signals containing odd numbered carriers in accordance with the alignment of the hyperframe to produce C-TONES-TTR, wherein the first response signals include periodic phase reversal; acquiring, by the remote DSL transceiver, TTR synchronization in accordance with the C-TONES-TTR.”

This embodiment of claim 1 describes a method to for extending handshaking range in a DSL system by helping to alleviate interference when a binder containing a number of twisted pair wires shared by xDSL modems and TCM-ISDN disturbers.

On page 4, the Office Action admits that the Long reference fails to disclose “transmitting initializing and response to handshaking in odd and even carriers.” In fact, the Long reference merely describes a specially defined TTR Indication signal to indicate the

boundaries of a FEXT and NEXT bitmap, as described in paragraph 26 of the Long reference, and nowhere discloses the elements of claim 1.

With respect to the Helms reference, the Office Action states in paragraph 5 on page 9 that, "However col 5 lines 50-66 clearly shows this feature as Helm discloses all odd multiple carriers may be used in the downstream path from the central office and even multiple carriers be used in the upstream path (or vice versa)." This statement is taken out of context and mischaracterizes the teachings of the Helms reference. The Helms reference describes aligning the frames transmitted by all CO modems, e.g. all frames transmitted by all CO modems start and end at the same time, as stated at column 6, lines 59 through 66. As stated at column 4, lines 61 through column 5, lines 8 in the Helms reference:

"It is a further principle of the present invention to align frames transmitted from the central office toward the subscriber. All frames transmitted by all central office modems are aligned and synchronized to begin at the same time as they are transmitted toward subscribers. That is, all frames transmitted by all central office modems to all subscribers (especially served on the same cable of twisted wire pairs) start and end at the same times. One way to accomplish the alignment is to provide a common shared timing signal to all CO modems from a common source. For example, the signal may comprise a train of narrow, for example, 1 microsecond pulses spaced by the period of a frame (for example, one millisecond). Each central office modem then would align its frames that are transmitted toward respective subscribers over different twisted wire cable pairs with this pulse train.

The pulse train from the common source may be accompanied by a higher frequency signal (for example, a sinusoid or a pulse train at the frequency specified in Section 6.9 of ANSI T1.413-1995) to which each modem could be synchronized. Alternatively, the pilot tone of 276 kHz specified at Section 6.9.1.2 might be applied as the shared resource. Either alternative will save the costs of providing an oscillator within each central office modem."

In addition, the Helms reference describes that the subscribers' modems are designed to align the frames that it transmits with the frames that it receives so that its transmitted frame coincides with its received frame, at column 7, lines 16 through 20. The Helms reference then later states at column 7, lines 52 through 56, "Optionally, the frequencies used by the central office and subscriber modems can be interspersed – either individually or in groups-to virtually eliminate near end crosstalk (NEXT), provided *that the frames are aligned as described above* (emphasis added)." Thus, the Helms reference discloses that the frames must be aligned using some type of pulse train from the common source. This type of alignment precludes the need for DSL handshaking and thus teaches away from the embodiment of DSL handshaking between the remote DSL transceiver and the central office transceiver of claim 1.

The Office Action further states that, "It should further be noted that the use of even numbered carriers for upstream and odd number carriers for downstream is simply a network parameter." However, the claims require more than "a network parameter", and Applicant's respectfully request citation of prior art showing this assertion. Furthermore, the Office Action's reasoning is not the legal basis for obviousness. The proper analysis is whether the claimed invention would have been obvious to one of ordinary skill in the art after consideration of all the facts. See 35 U.S.C. 103(a).

The dependent claims 2 through 7 add further patentable matter to Claim 1 and thus are further differentiated and patentable under 35 U.S.C. §103 over the Long reference in view of the Helms reference.

Independent Claim 8 and Dependent Claims 9 through 12

First, with respect to the Long reference, it fails to disclose or suggest the requirements of claim 8 of, "transmitting first signals for a predetermined period of time to initiate the DSL handshaking to produce R-ETONES-REQ, wherein the first signals comprise a plurality of even numbered carriers less one or more even numbered carriers, and includes periodic phase reversal; receiving first response signals containing odd numbered carriers in accordance with the alignment of a hyperframe to produce C-TONES-TTR; acquiring TTR synchronization in accordance with the C-TONES-TTR; upon acquiring TTR synchronization, transmitting second signals to produce R-TONE-TTR, wherein the second signals comprise a plurality of even numbered carriers less one or more even numbered carriers, and includes periodic phase

reversal.” On page 4, the Office Action admits that the Long reference fails to disclose “transmitting initializing and response to handshaking in odd and even carriers.” In fact, the Long reference merely describes a specially defined TTR Indication signal to indicate the boundaries of a FEXT and NEXT bitmap, as described in paragraph 26 of the Long reference and nowhere discloses the elements of claim 8.

With respect to the Helms reference, the Office Action states in paragraph 5 on page 9 that, “However col 5 lines 50-66 clearly shows this feature as Helm discloses all odd multiple carriers may be used in the downstream path from the central office and even multiple carriers be used in the upstream path (or vice versa).” This statement is taken out of context and mischaracterizes the teachings of the Helms reference. The Helms reference describes aligning the frames transmitted by all CO modems, e.g. all frames transmitted by all CO modems start and end at the same time, as stated at column 6, lines 59 through 66. In addition, the Helms reference describes that the subscribers’ modems are designed to align the frames that it transmits with the frames that it receives so that its transmitted frame coincides with its received frame, at column 7, lines 16 through 20. The Helms reference then later states at column 7, lines 52 through 56, “Optionally, the frequencies used by the central office and subscriber modems can be interspersed – either individually or in groups-to virtually eliminate near end crosstalk (NEXT), provided *that the frames are aligned as described above* (emphasis added).” Thus, the Helms reference discloses that the frames must be aligned using some type of pulse train from the common source. This type of alignment precludes the need for DSL handshaking and thus teaches away from the embodiment of DSL handshaking between the remote DSL transceiver and the central office transceiver of claim 8.

The Office Action further states that, “It should further be noted that the use of even numbered carriers for upstream and odd number carriers for downstream is simply a network parameter.” However, the claims require more than “a network parameter”, and Applicant’s respectfully request citation of prior art showing this assertion. Furthermore, the Office Action’s reasoning is not the legal basis for obviousness. The proper analysis is whether the claimed invention would have been obvious to one of ordinary skill in the art after consideration of all the facts. See 35 U.S.C. 103(a).

The dependent claims 9 through 12 add further patentable matter to Claim 8 and thus are further differentiated and patentable under 35 U.S.C. §103 over the Long reference in view of the Helms reference.

Independent Claim 13 and Dependent Claims 14 through 17

First, with respect to the Long reference, it fails to disclose or suggest the requirements of claim 13 of, “receiving first signals for a predetermined period of time to initiate the DSL handshaking to produce R-ETONES-REQ, wherein the first signals comprise a plurality of even numbered carriers less one or more even numbered carriers, and includes periodic phase reversal; detecting the R-ETONES-REQ to produce detected R-ETONES-REQ; determining alignment of a hyperframe in accordance with a Time Compression Multiplexing – Integrated Service Digital Network (TCM-ISDN) Timing Reference (TTR); transmitting first response signals in accordance with the alignment of the hyperframe to produce C-TONES-TTR, wherein the first response signals comprise a plurality of odd numbered carriers less one or more odd numbered carriers, and includes periodic phase reversal; receiving second signals to produce R-TONE-TTR, wherein the second signals comprise a plurality of even numbered carriers less one or more even numbered carriers, and includes periodic phase reversal; in response to the R-TONE-TTR, transmitting second response signals to produce C-GALFI-TTR, wherein the second response signals comprise a plurality of odd numbered carriers less one or more odd numbered carriers, and includes periodic phase reversal.” On page 4, the Office Action admits that the Long reference fails to disclose “transmitting initializing and response to handshaking in odd and even carriers.” In fact, the Long reference merely describes a specially defined TTR Indication signal to indicate the boundaries of a FEXT and NEXT bitmap, as described in paragraph 26 of the Long reference and nowhere discloses the elements of claim 13.

With respect to the Helms reference, the Office Action states in paragraph 5 on page 9 that, “However col 5 lines 50-66 clearly shows this feature as Helm discloses all odd multiple carriers may be used in the downstream path from the central office and even multiple carriers be used in the upstream path (or vice versa).” This statement is taken out of context and mischaracterizes the teachings of the Helms reference. The Helms reference describes aligning the frames transmitted by all CO modems, e.g. all frames transmitted by all CO modems start and end at the same time, as stated at column 6, lines 59 through 66. In addition, the Helms

reference describes that the subscribers' modems are designed to align the frames that it transmits with the frames that it receives so that its transmitted frame coincides with its received frame, at column 7, lines 16 through 20. The Helms reference then later states at column 7, lines 52 through 56, "Optionally, the frequencies used by the central office and subscriber modems can be interspersed – either individually or in groups-to virtually eliminate near end crosstalk (NEXT), provided *that the frames are aligned as described above* (emphasis added)." Thus, the Helms reference discloses that the frames must be aligned using some type of pulse train from the common source. This type of alignment precludes the need for DSL handshaking and thus teaches away from the embodiment of DSL handshaking between the remote DSL transceiver and the central office transceiver of claim 13.

The Office Action further states that, "It should further be noted that the use of even numbered carriers for upstream and odd number carriers for downstream is simply a network parameter." However, the claims require more than "a network parameter", and Applicant's respectfully request citation of prior art showing this assertion. Furthermore, the Office Action's reasoning is not the legal basis for obviousness. The proper analysis is whether the claimed invention would have been obvious to one of ordinary skill in the art after consideration of all the facts. See 35 U.S.C. 103(a).

The dependent claims 14 through 17 add further patentable matter to Claim 13 and thus are further differentiated and patentable under 35 U.S.C. §103 over the Long reference in view of the Helms reference.

Independent Claim 18 and Dependent Claims 19 through 22

First, with respect to the Long reference, it fails to disclose or suggest the requirements of claim 18 of, "memory operably coupled to the processing module, wherein the memory stores operational instructions that cause the processing module to: transmit first signals containing even numbered carriers for a predetermined period of time to initiate the DSL handshaking to produce R-ETONES-REQ, wherein the first signals include periodic phase reversal; receive first response signals containing odd numbered carriers in accordance with the alignment of a hyperframe to produce C-TONES-TTR, wherein the first response signals include periodic phase reversal; acquire TTR synchronization in accordance with the C-TONES-TTR; upon acquiring TTR synchronization, transmit second signals containing even numbered carriers to produce R-

TONE-TTR; receive second response signals containing odd numbered carriers to produce C-GALFI-TTR.” On page 4, the Office Action admits that the Long reference fails to disclose “transmitting initializing and response to handshaking in odd and even carriers.” In fact, the Long reference merely describes a specially defined TTR Indication signal to indicate the boundaries of a FEXT and NEXT bitmap, as described in paragraph 26 of the Long reference and nowhere discloses the elements of claim 18.

With respect to the Helms reference, the Office Action states in paragraph 5 on page 9 that, “However col 5 lines 50-66 clearly shows this feature as Helm discloses all odd multiple carriers may be used in the downstream path from the central office and even multiple carriers be used in the upstream path (or vice versa).” This statement is taken out of context and mischaracterizes the teachings of the Helms reference. The Helms reference describes aligning the frames transmitted by all CO modems, e.g. all frames transmitted by all CO modems start and end at the same time, as stated at column 6, lines 59 through 66. In addition, the Helms reference describes that the subscribers’ modems are designed to align the frames that it transmits with the frames that it receives so that its transmitted frame coincides with its received frame, at column 7, lines 16 through 20. The Helms reference then later states at column 7, lines 52 through 56, “Optionally, the frequencies used by the central office and subscriber modems can be interspersed – either individually or in groups-to virtually eliminate near end crosstalk (NEXT), provided *that the frames are aligned as described above* (emphasis added).” Thus, the Helms reference discloses that the frames must be aligned using some type of pulse train from the common source. This type of alignment precludes the need for DSL handshaking and thus teaches away from the embodiment of DSL handshaking between the remote DSL transceiver and the central office transceiver of claim 18.

The Office Action further states that, “It should further be noted that the use of even numbered carriers for upstream and odd number carriers for downstream is simply a network parameter.” However, the claims require more than “a network parameter”, and Applicant’s respectfully request citation of prior art showing this assertion. Furthermore, the Office Action’s reasoning is not the legal basis for obviousness. The proper analysis is whether the claimed invention would have been obvious to one of ordinary skill in the art after consideration of all the facts. See 35 U.S.C. 103(a).

The dependent claims 19 through 22 add further patentable matter to Claim 18 and thus are further differentiated and patentable under 35 U.S.C. §103 over the Long reference in view of the Helms reference.

Independent Claim 23 and Dependent Claims 24 through 27

First, with respect to the Long reference, it fails to disclose or suggest the requirements of claim 23 of, “memory operably coupled to the processing module, wherein the memory stores operational instructions that cause the processing module to: receive first signals containing even numbered carriers for a predetermined period of time to initiate the DSL handshaking to produce R-ETONES-REQ, wherein the first signals comprise even numbered carriers eight through thirty less, carriers twelve and fourteen; detect the R-ETONES-REQ to produce detected R-ETONES-REQ; determine alignment of a hyperframe in accordance with a Time Compression Multiplexing – Integrated Service Digital Network (TCM-ISDN) Timing Reference (TTR); transmit first response signals containing odd numbered carriers in accordance with the alignment of the hyperframe to produce C-TONES-TTR; receive second signals containing even numbered carriers to produce R-TONE-TTR.” On page 4, the Office Action admits that the Long reference fails to disclose “transmitting initializing and response to handshaking in odd and even carriers.” In fact, the Long reference merely describes a specially defined TTR Indication signal to indicate the boundaries of a FEXT and NEXT bitmap, as described in paragraph 26 of the Long reference and nowhere discloses the elements of claim 23.

With respect to the Helms reference, the Office Action states in paragraph 5 on page 9 that, “However col 5 lines 50-66 clearly shows this feature as Helm discloses all odd multiple carriers may be used in the downstream path from the central office and even multiple carriers be used in the upstream path (or vice versa).” This statement is taken out of context and mischaracterizes the teachings of the Helms reference. The Helms reference describes aligning the frames transmitted by all CO modems, e.g. all frames transmitted by all CO modems start and end at the same time, as stated at column 6, lines 59 through 66. In addition, the Helms reference describes that the subscribers’ modems are designed to align the frames that it transmits with the frames that it receives so that its transmitted frame coincides with its received frame, at column 7, lines 16 through 20. The Helms reference then later states at column 7, lines 52 through 56, “Optionally, the frequencies used by the central office and subscriber modems

can be interspersed – either individually or in groups-to virtually eliminate near end crosstalk (NEXT), provided *that the frames are aligned as described above* (emphasis added).” Thus, the Helms reference discloses that the frames must be aligned using some type of pulse train from the common source. This type of alignment precludes the need for DSL handshaking and thus teaches away from the embodiment of DSL handshaking between the remote DSL transceiver and the central office transceiver of claim 22.

The Office Action further states that, “It should further be noted that the use of even numbered carriers for upstream and odd number carriers for downstream is simply a network parameter.” However, the claims require more than “a network parameter”, and Applicant’s respectfully request citation of prior art showing this assertion. Furthermore, the Office Action’s reasoning is not the legal basis for obviousness. The proper analysis is whether the claimed invention would have been obvious to one of ordinary skill in the art after consideration of all the facts. See 35 U.S.C. 103(a).

The dependent claims 23 through 27 add further patentable matter to Claim 22 and thus are further differentiated and patentable under 35 U.S.C. §103 over the Long reference in view of the Helms reference.

CONCLUSION

For the above reasons, the foregoing amendment places the Application in condition for allowance. Therefore, it is respectfully requested that the rejection of the claims be withdrawn and full allowance granted. Should the Examiner have any further comments or suggestions, please contact Jessica Smith at (972) 240-5324.

Respectfully submitted,
GARLICK, HARRISON & MARKISON

/Jessica W. Smith/

Jessica W. Smith
Reg. No. 39,884

Dated: June 6, 2008

Garlick Harrison & Markison
P. O. Box 160727
Austin, TX 78716-0727
Phone: (972) 240-5324
Fax: (469) 366-6731